

LINIJA ZA IZRADU UD, CD, UW, CW PROFILA, PVC OJAČANJA....

ROLLFORMING LINE FOR UD, CD, UW, CW
PROFILES, REINFORCING METAL PROFILES.....



LINIJA ZA IZRADU UD,CD,UW,CW PROFILA,PVC OJAČANJA....

Linija se sastoji od odmotalice, mašine za profilisanje, makaza ili testere za odsecanje, prihvatnog stola i kontrolnog pulta.

Tehnički parametri:

- Kapacitet odmotalice: 2.000kg;
- Max radna širina: 300mm;
- Unutrašnji prečnik rolne: 480-750 mm;
- Pogonska snaga linije: 8,5 -10,5kw
- Brzina profilisanja: 20m/min;
- Tolerancija dužine: ± 1 mm;
- Debljina lima: 0,3-2mm;
- Broj stanica: 10-20;
- Prečnik osovina: 45-55mm;
- Materijal alata: 42CrMo4 nitriran na 64HRC;
- Materijal osovina: 42CrMo4 28 HRC;
- Materijal noževa: X210Cr12 58-60 HRC;
- Vrsta prenosa: lančani prenos;
- Vrsta odsecanja: hidraulične makaze ili kružna testera;
- Kontrola procesa: PLC EMERSON CONTROL TECHNIQUES;



ROLLFORMING LINE FOR UD,CD,UW,CW PROFILES,REINFORCING METAL PROFILES.....

The line is consist from decoiler,rollforming machine, cutting shear or saw,drop table and operation control panel.

Technical parameters:

- Capacity of decoiler: 2.000 kg;
- Max sheet width: 300 mm;
- Internal diameter of roll: 480-750 mm;
- Power input of line: 8,5-10,5 KW;
- Speed: 20 m/min;
- Longitudal cutoff tolerance: ± 1 mm;
- Sheet thickness: 0,3-2 mm;
- Number of stations: 10-20;
- Diametar of working shafts:45-55mm;
- Material of tools: 42CrMo4 nitriding 64HRC;
- Material of working shafts: 42CrMo4 28 HRC;
- Material of blades: X210Cr12 58-60 HRC;
- Power transmission: chains system;
- Type of cutting: hydraulic shear or circular saw;
- Operation Control Panel: PLC EMERSON CONTROL TECHNIQUES.



LINIJA ZA IZRADU UD, CD, UW, CW PROFILA, PVC OJAČANJA....

LINIJA ZA IZRADU UD, CD, UW, CW PROFILA, PVC OJAČANJA....

UD28	s=0,6mm		CD60	s=0,6mm		CD48	s=0,6mm		CW50	s=0,6mm	
CW75	s=0,6mm		CW100	s=0,6mm		UW50	s=0,6mm		UW75	s=0,6mm	
UW100	s=0,6mm		UC5035	s=0,55mm		L2323	s=0,25mm		L2313	s=0,25mm	
U-30x27,5	s=1,5mm		U-30x25	s=1,5mm		U-33x25	s=1,5mm		U-19x38	s=1,5mm	
U-35x45/48	s=2mm		U-38x47	s=2mm		U-38x45	s=2mm		U-36x50	s=2mm	
U-38x45	s=1,2mm		U-19x37	s=1,2mm		U-25,5x30	s=1,2mm		U-21x32,5	s=1,2mm	
U-26x40	s=1,2mm		U-28x26,5	s=1,2mm		U-28x28	s=1,2mm		U-29x26	s=1,5mm	
U-29,5x47,5	s=1,5mm		U-30x22	s=1,2mm		U-30x26	s=1,2mm s=1,5mm		U-30x28,5	s=2mm	
U-30x7/28	s=1,2mm		U-31x28	s=1,5mm		U-32x15/22	s=1,5mm		U-32x27	s=1,5mm	
U-32,5x40	s=2mm		U-30x30	s=1,2mm s=1,5mm		U-30x25	s=1,5mm		U-32x14/30	s=2mm	
U-59x31	s=1,2mm		U-50x30	s=2mm		U-32,5x42	s=1,2mm		U-32,5x40	s=2mm	
U-33x50	s=1,5mm		U-30x21	s=1,2mm s=1,5mm		U-34x27	s=1,2mm		U-35x28	s=1,2mm	
U-35x50	s=1,8mm		U-36x44,5	s=1,5mm		U-38x16/25	s=1,5mm		U-40x13/22	s=1,2mm	
U-36x12/27	s=1,2mm		U-36x18/26	s=1,5mm		U-40x15/28	s=1,2mm s=1,5mm		U-35x32	s=1,2mm	

